

## (12) United States Patent **Philipp**

# (10) Patent No.:

US 9,410,101 B2

(45) Date of Patent:

Aug. 9, 2016

## (54) PROCESS FOR OBTAINING ENERGY FROM ORGANIC-CONTAINING WASTE **MATERIALS**

(71) Applicant: Commerzialbank Mattersburg Im

Burgenland Aktiengesellschaft,

Mattersburg (AT)

(72) Inventor: **Franz Josef Philipp**, Forchtenstein (AT)

(73) Assignee: COMMERZIALBANK

MATTERSBURG IM BURGENLAND

AKTIENGESELLSCHAFT,

Mattersburg (AT)

(\*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 89 days.

(21) Appl. No.: 14/367,293

(22) PCT Filed: Dec. 20, 2012

(86) PCT No.: PCT/AT2012/050202

§ 371 (c)(1),

Jun. 20, 2014 (2) Date:

(87) PCT Pub. No.: WO2013/090967

PCT Pub. Date: Jun. 27, 2013

(65)**Prior Publication Data** 

> US 2014/0338255 A1 Nov. 20, 2014

(30)Foreign Application Priority Data

Dec. 21, 2011 (AT) ...... A 1860/2011

(51) **Int. Cl.** 

C10L 5/12 (2006.01)B01J 2/00 (2006.01)

(Continued)

(52) U.S. Cl. CPC . C10L 5/48 (2013.01); B09B 3/005 (2013.01); B09B 3/0041 (2013.01); B09B 3/0083 (2013.01); Y02E 50/30 (2013.01)

Field of Classification Search

CPC ....... C10L 5/48; B09B 3/0041; B09B 3/005; B09B 3/0083; Y02E 50/10; Y02E 50/30 

See application file for complete search history.

#### (56)**References Cited**

### U.S. PATENT DOCUMENTS

5,087,375 A \* 2/1992 Weinwurm ......... B01J 37/0018 5,888,256 A \* 3/1999 Morrison ...... C10L 5/40

(Continued)

### FOREIGN PATENT DOCUMENTS

389 474 B 5/1988 AΤ CH 688 990 A5 11/1994 (Continued)

Primary Examiner — Pamela H Weiss

(74) Attorney, Agent, or Firm — Lucas & Mercanti, LLP; Jonathan Myers

#### (57)ABSTRACT

A process is disclosed for obtaining energy from organiccontaining waste materials by (1) precomminuting the waste material and determining its ratio of carbonaceous material and silicatic material; (2) further measuring the constituents in the waste material to determine the ratio of carbonaceous material and silicatic material; (3) maintaining the ratio of carbonaceous material and silicatic material at about 90% to 10%; (4) adding phyllosilicate to the waste material, separating the resulting mixture into solid, liquid and gaseous phases, and pelletizing the solid phase; (5) pyrrolizing the pellets forming a second gaseous phase and a second solids phase; and (6) supplying the second gaseous phase to a tank, and separating the second solids phase into end product carbonaceous and silicatic materials, and recovering the carbonaceous materials.

#### 5 Claims, 1 Drawing Sheet

